



CoreLine Downlight – The clear choice for LED

CoreLine Downlight

The CoreLine Downlight range of recessed luminaires is designed to replace CFL-ni/CFL-i based downlight luminaires. Their attractive TCO helps customers to make the switch to LED. These luminaires create a natural lighting effect for use in general lighting applications. They also deliver instant energy savings and have a much longer lifetime, creating a real value-for-money and environmentally friendly solution. They are easy to install thanks to their standard cut-out size and push-in connectors. InterAct Ready luminaires with integrated wireless communications in this family available, to be used with InterAct gateways, sensors and software.

Benefits

- Reduced operating costs thanks to energy saving and longer lifetime
- One-to-one replacement, facilitating the switch from conventional to LED luminaires
- Suitable for professional applications thanks to DALI dimming and aluminum reflector

Features

- Available in 1100 and 2200 lumen versions
- Energy-efficient: up to 115 lm/W
- DALI and emergency lighting versions available
- Choice of color temperature: 3000 and 4000 K
- Protected glass available as an option (enables IP54 protection)

Application

- General lighting in corridors
- Retail stores
- Reception areas
- Indoor circulation areas

Specifications

CoreLine Downlight

Type	DN140B (versions with white and aluminum reflector)
Ceiling type	Plaster (board) ceiling
Light source	Non replaceable LED module
Power	9.5 W , 11.5 W (1100 lm) 19 W , 20.5 W , 22 W (2200 lm)
Efficacy	Up to 115 lm/W
Luminous flux	1100 lm 2200 lm
Correlated Color	3000 K (Warm white)
Temperature	4000 K (Neutral white)
Color Rendering Index	80
Median useful life L70B50	50,000 hours
Median useful life L80B50	30,000 hours
Median useful life L90B50	15,000 hours
Driver failure rate	1.5% per 5000 hours
Average ambient temperature	+25 °C
Operating temperature range	-20 to +40 °C

Driver	PSU: Built-in PSD and IA1: External, with DALI or Interact Ready interface
Mains voltage	230 or 240 V / 50-60 Hz
Dimming	DALI dimmable Dimmable via InterAct Not dimmable
Controls system input	DALI and Interact Ready
Material	Housing: plastic Reflector: plastic
Color	WH: white reflector / white rim C: aluminium reflector / white rim
Optic	Reflector, white / aluminum
Connection	Push-in connector with pull relief
Installation	Fixation by spring fasteners Through-wiring possible
Accessories	Protected glass also creating IP54
Remarks	DALI and IA1 versions have an external driver

Versions



CoreLine Downlight gen3 DN130B
luminaire, 1000 lumen version



CoreLine Downlight gen3 DN130B
luminaire, 2000 lumen version



CoreLine Downlight gen3 DN131B
luminaire, 1000 lumen version



CoreLine Downlight gen3 DN131B
luminaire, 2000 lumen version

CoreLine Downlight

Versions



CoreLine Downlight gen4 DN140B luminaire, 1100 lumen version, white reflector



CoreLine Downlight gen4 DN140B luminaire, 2200 lumen version, white reflector



CoreLine Downlight gen4 DN140B luminaire, 1100 lumen version, high gloss reflector



CoreLine Downlight gen4 DN140B luminaire, 2200 lumen version, high gloss reflector



CoreLine Downlight gen4 DN140B luminaire, 1100 lumen version, white reflector, IP54



CoreLine Downlight gen4 DN140B luminaire, 2200 lumen version, white reflector, IP54



CoreLine Downlight gen4 DN140B luminaire, 1100 lumen version, high gloss reflector, IP54



CoreLine Downlight gen4 DN140B luminaire, 2200 lumen version, high gloss reflector, IP54

Approval and Application

Mech. impact protection code	IK02
General Information	
Beam angle of light source	120 °
CE mark	CE mark
Driver included	Yes
Flammability mark	For mounting on normally flammable surfaces
Glow-wire test	Temperature 850 °C, duration 5 s
Light source replaceable	No
Number of gear units	1 unit
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

Application Conditions

Order Code	Full Product Name	Ambient temperature range	Maximum dim level	Suitable for random switching
910500457699	DN130B LED10S/830 PSU PI6 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457701	DN130B LED10S/830 PSED-E II WH	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500457724	DN130B LED10S/840 PSU PI6 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457725	DN130B LED10S/840 PSED-E II WH	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500458078	DN130B LED10S/830 PSU IP44 PI6 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500458079	DN130B LED10S/840 PSU IP44 PI6 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500458080	DN130B LED10S/830 PSED-E IP44 II WH	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500458081	DN130B LED10S/840 PSED-E IP44 II WH	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500457702	DN130B LED20S/830 PSU PI6 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457703	DN130B LED20S/830 PSED-E II WH	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500457726	DN130B LED20S/840 PSU PI6 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457727	DN130B LED20S/840 PSED-E II WH	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500458083	DN130B LED20S/840 PSU IP44 PI6 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500458084	DN130B LED20S/830 PSED-E IP44 II WH	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500458085	DN130B LED20S/840 PSED-E IP44 II WH	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500465262	DN130B LED20S/830 IA1 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)

Order Code	Full Product Name	Ambient temperature range	Maximum dim level	Suitable for random switching
910500465263	DN130B LED20S/840 IA1 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500465338	DN130B LED20S/830 ELB3 IA1 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500465339	DN130B LED20S/840 ELB3 IA1 WH	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457704	DN131B LED10S/830 PSU P16 ALU	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457705	DN131B LED10S/830 PSED-E II ALU	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500457728	DN131B LED10S/840 PSU P16 ALU	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457729	DN131B LED10S/840 PSED-E II ALU	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500458086	DN131B LED10S/830 PSU IP44 P16 ALU	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500458087	DN131B LED10S/840 PSU IP44 P16 ALU	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500458089	DN131B LED10S/840 PSED-E IP44 II ALU	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500457706	DN131B LED20S/830 PSU P16 ALU	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457707	DN131B LED20S/830 PSED-E II ALU	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500457730	DN131B LED20S/840 PSU P16 ALU	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500457731	DN131B LED20S/840 PSED-E II ALU	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)
910500458090	DN131B LED20S/830 PSU IP44 P16 ALU	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500458091	DN131B LED20S/840 PSU IP44 P16 ALU	-10 to +40 °C	-	Yes (relates to presence/movement detection and daylight harvesting)
910500458092	DN131B LED20S/830 PSED-E IP44 II ALU	-10 to +40 °C	1%	Yes (relates to presence/movement detection and daylight harvesting)

Order Code	Full Product Name	Ambient temperature range	Maximum dim level	Suitable for random switching
910500458093	DN131B LED20S/840 PSED-E IP44 II ALU	-10 to +40 °C	1%	Yes (relates to presence/ movement detection and daylight harvesting)
910500465264	DN131B LED20S/830 IA1 ALU	-10 to +40 °C	-	Yes (relates to presence/ movement detection and daylight harvesting)
910500465265	DN131B LED20S/840 IA1 ALU	-10 to +40 °C	-	Yes (relates to presence/ movement detection and daylight harvesting)
910500465340	DN131B LED20S/830 ELB3 IA1 ALU	-10 to +40 °C	-	Yes (relates to presence/ movement detection and daylight harvesting)
910500465341	DN131B LED20S/840 ELB3 IA1 ALU	-10 to +40 °C	-	Yes (relates to presence/ movement detection and daylight harvesting)
911401631005	DN140B LED10S/830 PSU WR PI6	-20 to +40 °C	Not applicable	No
911401631105	DN140B LED10S/840 PSU WR PI6	-20 to +40 °C	Not applicable	No
911401631205	DN140B LED10S/830 PSED-E WR	-20 to +40 °C	1%	No
911401631305	DN140B LED10S/840 PSED-E WR	-20 to +40 °C	1%	No
911401639405	DN140B LED10S/830 PSED-E WR ELB3	-20 to +40 °C	1%	No
911401639505	DN140B LED10S/840 PSED-E WR ELB3	-20 to +40 °C	1%	No
911401631405	DN140B LED20S/830 PSU WR PI6	-20 to +40 °C	Not applicable	No
911401631505	DN140B LED20S/840 PSU WR PI6	-20 to +40 °C	Not applicable	No
911401631605	DN140B LED20S/830 PSED-E WR	-20 to +40 °C	1%	No
911401631705	DN140B LED20S/840 PSED-E WR	-20 to +40 °C	1%	No
911401634205	DN140B LED20S/830 WR IA1	-20 to +40 °C	1%	No
911401634305	DN140B LED20S/840 WR IA1	-20 to +40 °C	1%	No
911401639605	DN140B LED20S/830 PSED-E WR ELB3	-20 to +40 °C	1%	No
911401639705	DN140B LED20S/840 PSED-E WR ELB3	-20 to +40 °C	1%	No
911401640205	DN140B LED20S/830 WR ELB3 IA1	-20 to +40 °C	1%	No
911401640305	DN140B LED20S/840 WR ELB3 IA1	-20 to +40 °C	1%	No
911401631805	DN140B LED10S/830 PSU C PI6	-20 to +40 °C	Not applicable	No
911401631905	DN140B LED10S/840 PSU C PI6	-20 to +40 °C	Not applicable	No
911401632005	DN140B LED10S/830 PSED-E C	-20 to +40 °C	1%	No

Order Code	Full Product Name	Ambient temperature range	Maximum dim level	Suitable for random switching
911401632105	DN140B LED10S/840 PSED-E C	-20 to +40 °C	1%	No
911401639805	DN140B LED10S/830 PSED-E C ELB3	-20 to +40 °C	1%	No
911401639905	DN140B LED10S/840 PSED-E C ELB3	-20 to +40 °C	1%	No
911401632205	DN140B LED20S/830 PSU C PI6	-20 to +40 °C	Not applicable	No
911401632305	DN140B LED20S/840 PSU C PI6	-20 to +40 °C	Not applicable	No
911401632405	DN140B LED20S/830 PSED-E C	-20 to +40 °C	1%	No
911401632505	DN140B LED20S/840 PSED-E C	-20 to +40 °C	1%	No
911401634405	DN140B LED20S/830 C IA1	-20 to +40 °C	1%	No
911401634505	DN140B LED20S/840 C IA1	-20 to +40 °C	1%	No
911401640005	DN140B LED20S/830 PSED-E C ELB3	-20 to +40 °C	1%	No
911401640105	DN140B LED20S/840 PSED-E C ELB3	-20 to +40 °C	1%	No
911401640405	DN140B LED20S/830 C ELB3 IA1	-20 to +40 °C	1%	No
911401640505	DN140B LED20S/840 C ELB3 IA1	-20 to +40 °C	1%	No
911401632605	DN140B LED10S/830 PSU WR IP54 PI6	-20 to +40 °C	Not applicable	No
911401632705	DN140B LED10S/840 PSU WR IP54 PI6	-20 to +40 °C	Not applicable	No
911401632805	DN140B LED10S/830 PSED-E WR IP54	-20 to +40 °C	1%	No
911401632905	DN140B LED10S/840 PSED-E WR IP54	-20 to +40 °C	1%	No
911401633005	DN140B LED20S/830 PSU WR IP54 PI6	-20 to +40 °C	Not applicable	No
911401633105	DN140B LED20S/840 PSU WR IP54 PI6	-20 to +40 °C	Not applicable	No
911401633205	DN140B LED20S/830 PSED-E WR IP54	-20 to +40 °C	1%	No
911401633305	DN140B LED20S/840 PSED-E WR IP54	-20 to +40 °C	1%	No
911401633405	DN140B LED10S/830 PSU C IP54 PI6	-20 to +40 °C	Not applicable	No
911401633505	DN140B LED10S/840 PSU C IP54 PI6	-20 to +40 °C	Not applicable	No
911401633605	DN140B LED10S/830 PSED-E C IP54	-20 to +40 °C	1%	No
911401633705	DN140B LED10S/840 PSED-E C IP54	-20 to +40 °C	1%	No
911401633805	DN140B LED20S/830 PSU C IP54 PI6	-20 to +40 °C	Not applicable	No

Order Code	Full Product Name	Ambient temperature range	Maximum dim level	Suitable for random switching
911401633905	DN140B LED20S/840 PSU C IP54 PI6	-20 to +40 °C	Not applicable	No
911401634005	DN140B LED20S/830 PSED-E C IP54	-20 to +40 °C	1%	No
911401634105	DN140B LED20S/840 PSED-E C IP54	-20 to +40 °C	1%	No

Approval and Application

Order Code	Full Product Name	Ingress protection code	Order Code	Full Product Name	Ingress protection code
910500457699	DN130B LED10S/830 PSU PI6 WH	IP20	911401631305	DN140B LED10S/840 PSED-E WR	IP20
910500457701	DN130B LED10S/830 PSED-E II WH	IP20	911401639405	DN140B LED10S/830 PSED-E WR ELB3	IP20
910500457724	DN130B LED10S/840 PSU PI6 WH	IP20	911401639505	DN140B LED10S/840 PSED-E WR ELB3	IP20
910500457725	DN130B LED10S/840 PSED-E II WH	IP20	911401631405	DN140B LED20S/830 PSU WR PI6	IP20
910500458078	DN130B LED10S/830 PSU IP44 PI6 WH	IP44	911401631505	DN140B LED20S/840 PSU WR PI6	IP20
910500458079	DN130B LED10S/840 PSU IP44 PI6 WH	IP44	911401631605	DN140B LED20S/830 PSED-E WR	IP20
910500458080	DN130B LED10S/830 PSED-E IP44 II WH	IP44	911401631705	DN140B LED20S/840 PSED-E WR	IP20
910500458081	DN130B LED10S/840 PSED-E IP44 II WH	IP44	911401634205	DN140B LED20S/830 WR IA1	IP20
910500457702	DN130B LED20S/830 PSU PI6 WH	IP20	911401634305	DN140B LED20S/840 WR IA1	IP20
910500457703	DN130B LED20S/830 PSED-E II WH	IP20	911401639605	DN140B LED20S/830 PSED-E WR ELB3	IP20
910500457726	DN130B LED20S/840 PSU PI6 WH	IP20	911401639705	DN140B LED20S/840 PSED-E WR ELB3	IP20
910500457727	DN130B LED20S/840 PSED-E II WH	IP20	911401640205	DN140B LED20S/830 WR ELB3 IA1	IP20
910500458083	DN130B LED20S/840 PSU IP44 PI6 WH	IP44	911401640305	DN140B LED20S/840 WR ELB3 IA1	IP20
910500458084	DN130B LED20S/830 PSED-E IP44 II WH	IP44	911401631805	DN140B LED10S/830 PSU C PI6	IP20
910500458085	DN130B LED20S/840 PSED-E IP44 II WH	IP44	911401631905	DN140B LED10S/840 PSU C PI6	IP20
910500465262	DN130B LED20S/830 IA1 WH	IP20	911401632005	DN140B LED10S/830 PSED-E C	IP20
910500465263	DN130B LED20S/840 IA1 WH	IP20	911401632105	DN140B LED10S/840 PSED-E C	IP20
910500465338	DN130B LED20S/830 ELB3 IA1 WH	IP20	911401639805	DN140B LED10S/830 PSED-E C ELB3	IP20
910500465339	DN130B LED20S/840 ELB3 IA1 WH	IP20	911401639905	DN140B LED10S/840 PSED-E C ELB3	IP20
910500457704	DN131B LED10S/830 PSU PI6 ALU	IP20	911401632205	DN140B LED20S/830 PSU C PI6	IP20
910500457705	DN131B LED10S/830 PSED-E II ALU	IP20	911401632305	DN140B LED20S/840 PSU C PI6	IP20
910500457728	DN131B LED10S/840 PSU PI6 ALU	IP20	911401632405	DN140B LED20S/830 PSED-E C	IP20
910500457729	DN131B LED10S/840 PSED-E II ALU	IP20	911401632505	DN140B LED20S/840 PSED-E C	IP20
910500458086	DN131B LED10S/830 PSU IP44 PI6 ALU	IP44	911401634405	DN140B LED20S/830 C IA1	IP20
910500458087	DN131B LED10S/840 PSU IP44 PI6 ALU	IP44	911401634505	DN140B LED20S/840 C IA1	IP20
910500458089	DN131B LED10S/840 PSED-E IP44 II ALU	IP44	911401640005	DN140B LED20S/830 PSED-E C ELB3	IP20
910500457706	DN131B LED20S/830 PSU PI6 ALU	IP20	911401640105	DN140B LED20S/840 PSED-E C ELB3	IP20
910500457707	DN131B LED20S/830 PSED-E II ALU	IP20	911401640405	DN140B LED20S/830 C ELB3 IA1	IP20
910500457730	DN131B LED20S/840 PSU PI6 ALU	IP20	911401640505	DN140B LED20S/840 C ELB3 IA1	IP20
910500457731	DN131B LED20S/840 PSED-E II ALU	IP20	911401632605	DN140B LED10S/830 PSU WR IP54 PI6	IP20/54
910500458090	DN131B LED20S/830 PSU IP44 PI6 ALU	IP44	911401632705	DN140B LED10S/840 PSU WR IP54 PI6	IP20/54
910500458091	DN131B LED20S/840 PSU IP44 PI6 ALU	IP44	911401632805	DN140B LED10S/830 PSED-E WR IP54	IP20/54
910500458092	DN131B LED20S/830 PSED-E IP44 II ALU	IP44	911401632905	DN140B LED10S/840 PSED-E WR IP54	IP20/54
910500458093	DN131B LED20S/840 PSED-E IP44 II ALU	IP44	911401633005	DN140B LED20S/830 PSU WR IP54 PI6	IP20/54
910500465264	DN131B LED20S/830 IA1 ALU	IP20	911401633105	DN140B LED20S/840 PSU WR IP54 PI6	IP20/54
910500465265	DN131B LED20S/840 IA1 ALU	IP20	911401633205	DN140B LED20S/830 PSED-E WR IP54	IP20/54
910500465340	DN131B LED20S/830 ELB3 IA1 ALU	IP20	911401633305	DN140B LED20S/840 PSED-E WR IP54	IP20/54
910500465341	DN131B LED20S/840 ELB3 IA1 ALU	IP20	911401633405	DN140B LED10S/830 PSU C IP54 PI6	IP20/54
911401631005	DN140B LED10S/830 PSU WR PI6	IP20	911401633505	DN140B LED10S/840 PSU C IP54 PI6	IP20/54
911401631105	DN140B LED10S/840 PSU WR PI6	IP20	911401633605	DN140B LED10S/830 PSED-E C IP54	IP20/54
911401631205	DN140B LED10S/830 PSED-E WR	IP20	911401633705	DN140B LED10S/840 PSED-E C IP54	IP20/54

CoreLine Downlight

Order Code	Full Product Name	Ingress protection code
911401633805	DN140B LED20S/830 PSU C IP54 PI6	IP20/54
911401633905	DN140B LED20S/840 PSU C IP54 PI6	IP20/54

Order Code	Full Product Name	Ingress protection code
911401634005	DN140B LED20S/830 PSED-E C IP54	IP20/54
911401634105	DN140B LED20S/840 PSED-E C IP54	IP20/54

Controls and Dimming

Order Code	Full Product Name	Dimmable
910500457699	DN130B LED10S/830 PSU PI6 WH	No
910500457701	DN130B LED10S/830 PSED-E II WH	Yes
910500457724	DN130B LED10S/840 PSU PI6 WH	No
910500457725	DN130B LED10S/840 PSED-E II WH	Yes
910500458078	DN130B LED10S/830 PSU IP44 PI6 WH	No
910500458079	DN130B LED10S/840 PSU IP44 PI6 WH	No
910500458080	DN130B LED10S/830 PSED-E IP44 II WH	Yes
910500458081	DN130B LED10S/840 PSED-E IP44 II WH	Yes
910500457702	DN130B LED20S/830 PSU PI6 WH	No
910500457703	DN130B LED20S/830 PSED-E II WH	Yes
910500457726	DN130B LED20S/840 PSU PI6 WH	No
910500457727	DN130B LED20S/840 PSED-E II WH	Yes
910500458083	DN130B LED20S/840 PSU IP44 PI6 WH	No
910500458084	DN130B LED20S/830 PSED-E IP44 II WH	Yes
910500458085	DN130B LED20S/840 PSED-E IP44 II WH	Yes
910500465262	DN130B LED20S/830 IA1 WH	No
910500465263	DN130B LED20S/840 IA1 WH	No
910500465338	DN130B LED20S/830 ELB3 IA1 WH	No
910500465339	DN130B LED20S/840 ELB3 IA1 WH	No
910500457704	DN131B LED10S/830 PSU PI6 ALU	No
910500457705	DN131B LED10S/830 PSED-E II ALU	Yes
910500457728	DN131B LED10S/840 PSU PI6 ALU	No
910500457729	DN131B LED10S/840 PSED-E II ALU	Yes
910500458086	DN131B LED10S/830 PSU IP44 PI6 ALU	No
910500458087	DN131B LED10S/840 PSU IP44 PI6 ALU	No
910500458089	DN131B LED10S/840 PSED-E IP44 II ALU	Yes
910500457706	DN131B LED20S/830 PSU PI6 ALU	No
910500457707	DN131B LED20S/830 PSED-E II ALU	Yes
910500457730	DN131B LED20S/840 PSU PI6 ALU	No
910500457731	DN131B LED20S/840 PSED-E II ALU	Yes
910500458090	DN131B LED20S/830 PSU IP44 PI6 ALU	No
910500458091	DN131B LED20S/840 PSU IP44 PI6 ALU	No
910500458092	DN131B LED20S/830 PSED-E IP44 II ALU	Yes
910500458093	DN131B LED20S/840 PSED-E IP44 II ALU	Yes
910500465264	DN131B LED20S/830 IA1 ALU	No
910500465265	DN131B LED20S/840 IA1 ALU	No
910500465340	DN131B LED20S/830 ELB3 IA1 ALU	No
910500465341	DN131B LED20S/840 ELB3 IA1 ALU	No
911401631005	DN140B LED10S/830 PSU WR PI6	No
911401631105	DN140B LED10S/840 PSU WR PI6	No
911401631205	DN140B LED10S/830 PSED-E WR	Yes
911401631305	DN140B LED10S/840 PSED-E WR	Yes
911401639405	DN140B LED10S/830 PSED-E WR ELB3	Yes

Order Code	Full Product Name	Dimmable
911401639505	DN140B LED10S/840 PSED-E WR ELB3	Yes
911401631405	DN140B LED20S/830 PSU WR PI6	No
911401631505	DN140B LED20S/840 PSU WR PI6	No
911401631605	DN140B LED20S/830 PSED-E WR	Yes
911401631705	DN140B LED20S/840 PSED-E WR	Yes
911401634205	DN140B LED20S/830 WR IA1	Yes
911401634305	DN140B LED20S/840 WR IA1	Yes
911401639605	DN140B LED20S/830 PSED-E WR ELB3	Yes
911401639705	DN140B LED20S/840 PSED-E WR ELB3	Yes
911401640205	DN140B LED20S/830 WR ELB3 IA1	Yes
911401640305	DN140B LED20S/840 WR ELB3 IA1	Yes
911401631805	DN140B LED10S/830 PSU C PI6	No
911401631905	DN140B LED10S/840 PSU C PI6	No
911401632005	DN140B LED10S/830 PSED-E C	Yes
911401632105	DN140B LED10S/840 PSED-E C	Yes
911401639805	DN140B LED10S/830 PSED-E C ELB3	Yes
911401639905	DN140B LED10S/840 PSED-E C ELB3	Yes
911401632205	DN140B LED20S/830 PSU C PI6	No
911401632305	DN140B LED20S/840 PSU C PI6	No
911401632405	DN140B LED20S/830 PSED-E C	Yes
911401632505	DN140B LED20S/840 PSED-E C	Yes
911401634405	DN140B LED20S/830 C IA1	Yes
911401634505	DN140B LED20S/840 C IA1	Yes
911401640005	DN140B LED20S/830 PSED-E C ELB3	Yes
911401640105	DN140B LED20S/840 PSED-E C ELB3	Yes
911401640405	DN140B LED20S/830 C ELB3 IA1	Yes
911401640505	DN140B LED20S/840 C ELB3 IA1	Yes
911401632605	DN140B LED10S/830 PSU WR IP54 PI6	No
911401632705	DN140B LED10S/840 PSU WR IP54 PI6	No
911401632805	DN140B LED10S/830 PSED-E WR IP54	Yes
911401632905	DN140B LED10S/840 PSED-E WR IP54	Yes
911401633005	DN140B LED20S/830 PSU WR IP54 PI6	No
911401633105	DN140B LED20S/840 PSU WR IP54 PI6	No
911401633205	DN140B LED20S/830 PSED-E WR IP54	Yes
911401633305	DN140B LED20S/840 PSED-E WR IP54	Yes
911401633405	DN140B LED10S/830 PSU C IP54 PI6	No
911401633505	DN140B LED10S/840 PSU C IP54 PI6	No
911401633605	DN140B LED10S/830 PSED-E C IP54	Yes
911401633705	DN140B LED10S/840 PSED-E C IP54	Yes
911401633805	DN140B LED20S/830 PSU C IP54 PI6	No
911401633905	DN140B LED20S/840 PSU C IP54 PI6	No
911401634005	DN140B LED20S/830 PSED-E C IP54	Yes
911401634105	DN140B LED20S/840 PSED-E C IP54	Yes

Operating and Electrical

CoreLine Downlight

Order Code	Full Product Name	Input Voltage
910500457699	DN130B LED10S/830 PSU PI6 WH	220 to 240 V
910500457701	DN130B LED10S/830 PSED-E II WH	220 to 240 V
910500457724	DN130B LED10S/840 PSU PI6 WH	220 to 240 V
910500457725	DN130B LED10S/840 PSED-E II WH	220 to 240 V
910500458078	DN130B LED10S/830 PSU IP44 PI6 WH	220 to 240 V
910500458079	DN130B LED10S/840 PSU IP44 PI6 WH	220 to 240 V
910500458080	DN130B LED10S/830 PSED-E IP44 II WH	220 to 240 V
910500458081	DN130B LED10S/840 PSED-E IP44 II WH	220 to 240 V
910500457702	DN130B LED20S/830 PSU PI6 WH	220 to 240 V
910500457703	DN130B LED20S/830 PSED-E II WH	220 to 240 V
910500457726	DN130B LED20S/840 PSU PI6 WH	220 to 240 V
910500457727	DN130B LED20S/840 PSED-E II WH	220 to 240 V
910500458083	DN130B LED20S/840 PSU IP44 PI6 WH	220 to 240 V
910500458084	DN130B LED20S/830 PSED-E IP44 II WH	220 to 240 V
910500458085	DN130B LED20S/840 PSED-E IP44 II WH	220 to 240 V
910500465262	DN130B LED20S/830 IA1 WH	220 to 240 V
910500465263	DN130B LED20S/840 IA1 WH	220 to 240 V
910500465338	DN130B LED20S/830 ELB3 IA1 WH	220 to 240 V
910500465339	DN130B LED20S/840 ELB3 IA1 WH	220 to 240 V
910500457704	DN131B LED10S/830 PSU PI6 ALU	220 to 240 V
910500457705	DN131B LED10S/830 PSED-E II ALU	220 to 240 V
910500457728	DN131B LED10S/840 PSU PI6 ALU	220 to 240 V
910500457729	DN131B LED10S/840 PSED-E II ALU	220 to 240 V
910500458086	DN131B LED10S/830 PSU IP44 PI6 ALU	220 to 240 V
910500458087	DN131B LED10S/840 PSU IP44 PI6 ALU	220 to 240 V
910500458089	DN131B LED10S/840 PSED-E IP44 II ALU	220 to 240 V
910500457706	DN131B LED20S/830 PSU PI6 ALU	220 to 240 V
910500457707	DN131B LED20S/830 PSED-E II ALU	220 to 240 V
910500457730	DN131B LED20S/840 PSU PI6 ALU	220 to 240 V
910500457731	DN131B LED20S/840 PSED-E II ALU	220 to 240 V
910500458090	DN131B LED20S/830 PSU IP44 PI6 ALU	220 to 240 V
910500458091	DN131B LED20S/840 PSU IP44 PI6 ALU	220 to 240 V
910500458092	DN131B LED20S/830 PSED-E IP44 II ALU	220 to 240 V
910500458093	DN131B LED20S/840 PSED-E IP44 II ALU	220 to 240 V
910500465264	DN131B LED20S/830 IA1 ALU	220 to 240 V
910500465265	DN131B LED20S/840 IA1 ALU	220 to 240 V
910500465340	DN131B LED20S/830 ELB3 IA1 ALU	220 to 240 V
910500465341	DN131B LED20S/840 ELB3 IA1 ALU	220 to 240 V
911401631005	DN140B LED10S/830 PSU WR PI6	220-240 V
911401631105	DN140B LED10S/840 PSU WR PI6	220-240 V
911401631205	DN140B LED10S/830 PSED-E WR	220-240 V
911401631305	DN140B LED10S/840 PSED-E WR	220-240 V
911401639405	DN140B LED10S/830 PSED-E WR ELB3	220-240 V

Order Code	Full Product Name	Input Voltage
911401639505	DN140B LED10S/840 PSED-E WR ELB3	220-240 V
911401631405	DN140B LED20S/830 PSU WR PI6	220-240 V
911401631505	DN140B LED20S/840 PSU WR PI6	220-240 V
911401631605	DN140B LED20S/830 PSED-E WR	220-240 V
911401631705	DN140B LED20S/840 PSED-E WR	220-240 V
911401634205	DN140B LED20S/830 WR IA1	220-240 V
911401634305	DN140B LED20S/840 WR IA1	220-240 V
911401639605	DN140B LED20S/830 PSED-E WR ELB3	220-240 V
911401639705	DN140B LED20S/840 PSED-E WR ELB3	220-240 V
911401640205	DN140B LED20S/830 WR ELB3 IA1	220-240 V
911401640305	DN140B LED20S/840 WR ELB3 IA1	220-240 V
911401631805	DN140B LED10S/830 PSU C PI6	220-240 V
911401631905	DN140B LED10S/840 PSU C PI6	220-240 V
911401632005	DN140B LED10S/830 PSED-E C	220-240 V
911401632105	DN140B LED10S/840 PSED-E C	220-240 V
911401639805	DN140B LED10S/830 PSED-E C ELB3	220-240 V
911401639905	DN140B LED10S/840 PSED-E C ELB3	220-240 V
911401632205	DN140B LED20S/830 PSU C PI6	220-240 V
911401632305	DN140B LED20S/840 PSU C PI6	220-240 V
911401632405	DN140B LED20S/830 PSED-E C	220-240 V
911401632505	DN140B LED20S/840 PSED-E C	220-240 V
911401634405	DN140B LED20S/830 C IA1	220-240 V
911401634505	DN140B LED20S/840 C IA1	220-240 V
911401640005	DN140B LED20S/830 PSED-E C ELB3	220-240 V
911401640105	DN140B LED20S/840 PSED-E C ELB3	220-240 V
911401640405	DN140B LED20S/830 C ELB3 IA1	220-240 V
911401640505	DN140B LED20S/840 C ELB3 IA1	220-240 V
911401632605	DN140B LED10S/830 PSU WR IP54 PI6	220-240 V
911401632705	DN140B LED10S/840 PSU WR IP54 PI6	220-240 V
911401632805	DN140B LED10S/830 PSED-E WR IP54	220-240 V
911401632905	DN140B LED10S/840 PSED-E WR IP54	220-240 V
911401633005	DN140B LED20S/830 PSU WR IP54 PI6	220-240 V
911401633105	DN140B LED20S/840 PSU WR IP54 PI6	220-240 V
911401633205	DN140B LED20S/830 PSED-E WR IP54	220-240 V
911401633305	DN140B LED20S/840 PSED-E WR IP54	220-240 V
911401633405	DN140B LED10S/830 PSU C IP54 PI6	220-240 V
911401633505	DN140B LED10S/840 PSU C IP54 PI6	220-240 V
911401633605	DN140B LED10S/830 PSED-E C IP54	220-240 V
911401633705	DN140B LED10S/840 PSED-E C IP54	220-240 V
911401633805	DN140B LED20S/830 PSU C IP54 PI6	220-240 V
911401633905	DN140B LED20S/840 PSU C IP54 PI6	220-240 V
911401634005	DN140B LED20S/830 PSED-E C IP54	220-240 V
911401634105	DN140B LED20S/840 PSED-E C IP54	220-240 V

General Information (1/2)

Order Code	Full Product Name	Protection class IEC	Optical	ENE C	Lamp
			cover/lens type	mark	family code
910500457699	DN130B LED10S/830 PSU PI6 WH	Safety class I	Acrylic - bowl/cover frosted	-	LED10S

Order Code	Full Product Name	Protection class IEC	Optical	ENE C	Lamp
			cover/lens type	mark	family code
910500457701	DN130B LED10S/830 PSED-E II WH	Safety class II	Acrylic - bowl/cover frosted	-	LED10S

CoreLine Downlight

Order Code	Full Product Name	Protection class IEC	Optical cover/lens type	ENEC mark	Lamp family code
910500457724	DN130B LED10S/840 PSU PI6 WH	Safety class I	Acrylic bowl/cover frosted	-	LED10S
910500457725	DN130B LED10S/840 PSED-E II WH	Safety class II	Acrylic bowl/cover frosted	-	LED10S
910500458078	DN130B LED10S/830 PSU IP44 PI6 WH	Safety class I	Acrylic bowl/cover frosted	-	LED10S
910500458079	DN130B LED10S/840 PSU IP44 PI6 WH	Safety class I	Acrylic bowl/cover frosted	-	LED10S
910500458080	DN130B LED10S/830 PSED-E IP44 II WH	Safety class II	Acrylic bowl/cover frosted	-	LED10S
910500458081	DN130B LED10S/840 PSED-E IP44 II WH	Safety class II	Acrylic bowl/cover frosted	-	LED10S
910500457702	DN130B LED20S/830 PSU PI6 WH	Safety class I	Acrylic bowl/cover frosted	-	LED20S
910500457703	DN130B LED20S/830 PSED-E II WH	Safety class II	Acrylic bowl/cover frosted	-	LED20S
910500457726	DN130B LED20S/840 PSU PI6 WH	Safety class I	Acrylic bowl/cover frosted	-	LED20S
910500457727	DN130B LED20S/840 PSED-E II WH	Safety class II	Acrylic bowl/cover frosted	-	LED20S
910500458083	DN130B LED20S/840 PSU IP44 PI6 WH	Safety class I	Acrylic bowl/cover frosted	-	LED20S
910500458084	DN130B LED20S/830 PSED-E IP44 II WH	Safety class II	Acrylic bowl/cover frosted	-	LED20S
910500458085	DN130B LED20S/840 PSED-E IP44 II WH	Safety class II	Acrylic bowl/cover frosted	-	LED20S
910500465262	DN130B LED20S/830 IA1 WH	Safety class II	-	ENEC mark	-
910500465263	DN130B LED20S/840 IA1 WH	Safety class II	-	ENEC mark	-
910500465338	DN130B LED20S/830 ELB3 IA1 WH	Safety class II	-	-	-
910500465339	DN130B LED20S/840 ELB3 IA1 WH	Safety class II	-	-	-
910500457704	DN131B LED10S/830 PSU PI6 ALU	Safety class I	Acrylic bowl/cover frosted	-	LED10S

Order Code	Full Product Name	Protection class IEC	Optical cover/lens type	ENEC mark	Lamp family code
910500457705	DN131B LED10S/830 PSED-E II ALU	Safety class II	Acrylic bowl/cover frosted	-	LED10S
910500457728	DN131B LED10S/840 PSU PI6 ALU	Safety class I	Acrylic bowl/cover frosted	-	LED10S
910500457729	DN131B LED10S/840 PSED-E II ALU	Safety class II	Acrylic bowl/cover frosted	-	LED10S
910500458086	DN131B LED10S/830 PSU IP44 PI6 ALU	Safety class I	Acrylic bowl/cover frosted	-	LED10S
910500458087	DN131B LED10S/840 PSU IP44 PI6 ALU	Safety class I	Acrylic bowl/cover frosted	-	LED10S
910500458089	DN131B LED10S/840 PSED-E IP44 II ALU	Safety class II	Acrylic bowl/cover frosted	-	LED10S
910500457706	DN131B LED20S/830 PSU PI6 ALU	Safety class I	Acrylic bowl/cover frosted	-	LED20S
910500457707	DN131B LED20S/830 PSED-E II ALU	Safety class II	Acrylic bowl/cover frosted	-	LED20S
910500457730	DN131B LED20S/840 PSU PI6 ALU	Safety class I	Acrylic bowl/cover frosted	-	LED20S
910500457731	DN131B LED20S/840 PSED-E II ALU	Safety class II	Acrylic bowl/cover frosted	-	LED20S
910500458090	DN131B LED20S/830 PSU IP44 PI6 ALU	Safety class I	Acrylic bowl/cover frosted	-	LED20S
910500458091	DN131B LED20S/840 PSU IP44 PI6 ALU	Safety class I	Acrylic bowl/cover frosted	-	LED20S
910500458092	DN131B LED20S/830 PSED-E IP44 II ALU	Safety class II	Acrylic bowl/cover frosted	-	LED20S
910500458093	DN131B LED20S/840 PSED-E IP44 II ALU	Safety class II	Acrylic bowl/cover frosted	-	LED20S
910500465264	DN131B LED20S/830 IA1 ALU	Safety class II	-	ENEC mark	-
910500465265	DN131B LED20S/840 IA1 ALU	Safety class II	-	ENEC mark	-
910500465340	DN131B LED20S/830 ELB3 IA1 ALU	Safety class II	-	-	-
910500465341	DN131B LED20S/840 ELB3 IA1 ALU	Safety class II	-	-	-

CoreLine Downlight

Order Code	Full Product Name	Protection class IEC	Optical cover/lens type	ENEC mark	Lamp family code
911401631005	DN140B LED10S/830 PSU WR PI6	Safety class I	-	-	-
911401631105	DN140B LED10S/840 PSU WR PI6	Safety class I	-	-	-
911401631205	DN140B LED10S/830 PSED-E WR	Safety class I	-	-	-
911401631305	DN140B LED10S/840 PSED-E WR	Safety class I	-	-	-
911401639405	DN140B LED10S/830 PSED-E WR ELB3	Safety class I	-	-	-
911401639505	DN140B LED10S/840 PSED-E WR ELB3	Safety class I	-	-	-
911401631405	DN140B LED20S/830 PSU WR PI6	Safety class I	-	-	-
911401631505	DN140B LED20S/840 PSU WR PI6	Safety class I	-	-	-
911401631605	DN140B LED20S/830 PSED-E WR	Safety class I	-	-	-
911401631705	DN140B LED20S/840 PSED-E WR	Safety class I	-	-	-
911401634205	DN140B LED20S/830 WR IA1	Safety class I	-	-	-
911401634305	DN140B LED20S/840 WR IA1	Safety class I	-	-	-
911401639605	DN140B LED20S/830 PSED-E WR ELB3	Safety class I	-	-	-
911401639705	DN140B LED20S/840 PSED-E WR ELB3	Safety class I	-	-	-
911401640205	DN140B LED20S/830 WR ELB3 IA1	Safety class I	-	-	-
911401640305	DN140B LED20S/840 WR ELB3 IA1	Safety class I	-	-	-
911401631805	DN140B LED10S/830 PSU C PI6	Safety class I	-	-	-
911401631905	DN140B LED10S/840 PSU C PI6	Safety class I	-	-	-
911401632005	DN140B LED10S/830 PSED-E C	Safety class I	-	-	-
911401632105	DN140B LED10S/840 PSED-E C	Safety class I	-	-	-
911401639805	DN140B LED10S/830 PSED-E C ELB3	Safety class I	-	-	-
911401639905	DN140B LED10S/840 PSED-E C ELB3	Safety class I	-	-	-
911401632205	DN140B LED20S/830 PSU C PI6	Safety class I	-	-	-
911401632305	DN140B LED20S/840 PSU C PI6	Safety class I	-	-	-

Order Code	Full Product Name	Protection class IEC	Optical cover/lens type	ENEC mark	Lamp family code
911401632405	DN140B LED20S/830 PSED-E C	Safety class I	-	-	-
911401632505	DN140B LED20S/840 PSED-E C	Safety class I	-	-	-
911401634405	DN140B LED20S/830 C IA1	Safety class I	-	-	-
911401634505	DN140B LED20S/840 C IA1	Safety class I	-	-	-
911401640005	DN140B LED20S/830 PSED-E C ELB3	Safety class I	-	-	-
911401640105	DN140B LED20S/840 PSED-E C ELB3	Safety class I	-	-	-
911401640405	DN140B LED20S/830 C ELB3 IA1	Safety class I	-	-	-
911401640505	DN140B LED20S/840 C ELB3 IA1	Safety class I	-	-	-
911401632605	DN140B LED10S/830 PSU WR IP54 PI6	Safety class I	-	-	-
911401632705	DN140B LED10S/840 PSU WR IP54 PI6	Safety class I	-	-	-
911401632805	DN140B LED10S/830 PSED-E WR IP54	Safety class I	-	-	-
911401632905	DN140B LED10S/840 PSED-E WR IP54	Safety class I	-	-	-
911401633005	DN140B LED20S/830 PSU WR IP54 PI6	Safety class I	-	-	-
911401633105	DN140B LED20S/840 PSU WR IP54 PI6	Safety class I	-	-	-
911401633205	DN140B LED20S/830 PSED-E WR IP54	Safety class I	-	-	-
911401633305	DN140B LED20S/840 PSED-E WR IP54	Safety class I	-	-	-
911401633405	DN140B LED10S/830 PSU C IP54 PI6	Safety class I	-	-	-
911401633505	DN140B LED10S/840 PSU C IP54 PI6	Safety class I	-	-	-
911401633605	DN140B LED10S/830 PSED-E C IP54	Safety class I	-	-	-
911401633705	DN140B LED10S/840 PSED-E C IP54	Safety class I	-	-	-
911401633805	DN140B LED20S/830 PSU C IP54 PI6	Safety class I	-	-	-
911401633905	DN140B LED20S/840 PSU C IP54 PI6	Safety class I	-	-	-
911401634005	DN140B LED20S/830 PSED-E C IP54	Safety class I	-	-	-
911401634105	DN140B LED20S/840 PSED-E C IP54	Safety class I	-	-	-

General Information (2/2)

CoreLine Downlight

Order Code	Full Product Name	Number of light sources	Optic type	Product Family Code
910500457699	DN130B LED10S/830 PSU PI6 WH	1 pc	Wide beam	DN130B
910500457701	DN130B LED10S/830 PSED-E II WH	1 pc	Wide beam	DN130B
910500457724	DN130B LED10S/840 PSU PI6 WH	1 pc	Wide beam	DN130B
910500457725	DN130B LED10S/840 PSED-E II WH	1 pc	Wide beam	DN130B
910500458078	DN130B LED10S/830 PSU IP44 PI6 WH	1 pc	Wide beam	DN130B
910500458079	DN130B LED10S/840 PSU IP44 PI6 WH	1 pc	Wide beam	DN130B
910500458080	DN130B LED10S/830 PSED-E IP44 II WH	1 pc	Wide beam	DN130B
910500458081	DN130B LED10S/840 PSED-E IP44 II WH	1 pc	Wide beam	DN130B
910500457702	DN130B LED20S/830 PSU PI6 WH	1 pc	Wide beam	DN130B
910500457703	DN130B LED20S/830 PSED-E II WH	1 pc	Wide beam	DN130B
910500457726	DN130B LED20S/840 PSU PI6 WH	1 pc	Wide beam	DN130B
910500457727	DN130B LED20S/840 PSED-E II WH	1 pc	Wide beam	DN130B
910500458083	DN130B LED20S/840 PSU IP44 PI6 WH	1 pc	Wide beam	DN130B
910500458084	DN130B LED20S/830 PSED-E IP44 II WH	1 pc	Wide beam	DN130B
910500458085	DN130B LED20S/840 PSED-E IP44 II WH	1 pc	Wide beam	DN130B
910500465262	DN130B LED20S/830 IA1 WH	-	White reflector without louver	DN130B
910500465263	DN130B LED20S/840 IA1 WH	-	White reflector without louver	DN130B
910500465338	DN130B LED20S/830 ELB3 IA1 WH	-	White reflector without louver	DN130B
910500465339	DN130B LED20S/840 ELB3 IA1 WH	-	White reflector without louver	DN130B
910500457704	DN131B LED10S/830 PSU PI6 ALU	1 pc	Wide beam	DN131B
910500457705	DN131B LED10S/830 PSED-E II ALU	1 pc	Wide beam	DN131B
910500457728	DN131B LED10S/840 PSU PI6 ALU	1 pc	Wide beam	DN131B
910500457729	DN131B LED10S/840 PSED-E II ALU	1 pc	Wide beam	DN131B
910500458086	DN131B LED10S/830 PSU IP44 PI6 ALU	1 pc	Wide beam	DN131B
910500458087	DN131B LED10S/840 PSU IP44 PI6 ALU	1 pc	Wide beam	DN131B

Order Code	Full Product Name	Number of light sources	Optic type	Product Family Code
910500458089	DN131B LED10S/840 PSED-E IP44 II ALU	1 pc	Wide beam	DN131B
910500457706	DN131B LED20S/830 PSU PI6 ALU	1 pc	Wide beam	DN131B
910500457707	DN131B LED20S/830 PSED-E II ALU	1 pc	Wide beam	DN131B
910500457730	DN131B LED20S/840 PSU PI6 ALU	1 pc	Wide beam	DN131B
910500457731	DN131B LED20S/840 PSED-E II ALU	1 pc	Wide beam	DN131B
910500458090	DN131B LED20S/830 PSU IP44 PI6 ALU	1 pc	Wide beam	DN131B
910500458091	DN131B LED20S/840 PSU IP44 PI6 ALU	1 pc	Wide beam	DN131B
910500458092	DN131B LED20S/830 PSED-E IP44 II ALU	1 pc	Wide beam	DN131B
910500458093	DN131B LED20S/840 PSED-E IP44 II ALU	1 pc	Wide beam	DN131B
910500465264	DN131B LED20S/830 IA1 ALU	-	High-gloss mirror	DN131B
910500465265	DN131B LED20S/840 IA1 ALU	-	High-gloss mirror	DN131B
910500465340	DN131B LED20S/830 ELB3 IA1 ALU	-	High-gloss mirror	DN131B
910500465341	DN131B LED20S/840 ELB3 IA1 ALU	-	High-gloss mirror	DN131B
911401631005	DN140B LED10S/830 PSU WR PI6	-	White reflector without louver	-
911401631105	DN140B LED10S/840 PSU WR PI6	-	White reflector without louver	-
911401631205	DN140B LED10S/830 PSED-E WR	-	White reflector without louver	-
911401631305	DN140B LED10S/840 PSED-E WR	-	White reflector without louver	-
911401639405	DN140B LED10S/830 PSED-E WR ELB3	-	White reflector without louver	-
911401639505	DN140B LED10S/840 PSED-E WR ELB3	-	White reflector without louver	-
911401631405	DN140B LED20S/830 PSU WR PI6	-	White reflector without louver	-
911401631505	DN140B LED20S/840 PSU WR PI6	-	White reflector without louver	-
911401631605	DN140B LED20S/830 PSED-E WR	-	White reflector without louver	-
911401631705	DN140B LED20S/840 PSED-E WR	-	White reflector without louver	-
911401634205	DN140B LED20S/830 WR IA1	-	White reflector without louver	-
911401634305	DN140B LED20S/840 WR IA1	-	White reflector without louver	-
911401639605	DN140B LED20S/830 PSED-E WR ELB3	-	White reflector without louver	-

CoreLine Downlight

Order Code	Full Product Name	Number of		Product Family Code
		light sources	Optic type	
911401639705	DN140B LED20S/840 PSED-E WR ELB3	-	White reflector without louver	-
911401640205	DN140B LED20S/830 WR ELB3 IA1	-	White reflector without louver	-
911401640305	DN140B LED20S/840 WR ELB3 IA1	-	White reflector without louver	-
911401631805	DN140B LED10S/830 PSU C PI6	-	High-gloss mirror	-
911401631905	DN140B LED10S/840 PSU C PI6	-	High-gloss mirror	-
911401632005	DN140B LED10S/830 PSED-E C	-	High-gloss mirror	-
911401632105	DN140B LED10S/840 PSED-E C	-	High-gloss mirror	-
911401639805	DN140B LED10S/830 PSED-E C ELB3	-	High-gloss mirror	-
911401639905	DN140B LED10S/840 PSED-E C ELB3	-	High-gloss mirror	-
911401632205	DN140B LED20S/830 PSU C PI6	-	High-gloss mirror	-
911401632305	DN140B LED20S/840 PSU C PI6	-	High-gloss mirror	-
911401632405	DN140B LED20S/830 PSED-E C	-	High-gloss mirror	-
911401632505	DN140B LED20S/840 PSED-E C	-	High-gloss mirror	-
911401634405	DN140B LED20S/830 C IA1	-	High-gloss mirror	-
911401634505	DN140B LED20S/840 C IA1	-	High-gloss mirror	-
911401640005	DN140B LED20S/830 PSED-E C ELB3	-	High-gloss mirror	-
911401640105	DN140B LED20S/840 PSED-E C ELB3	-	High-gloss mirror	-
911401640405	DN140B LED20S/830 C ELB3 IA1	-	High-gloss mirror	-

Order Code	Full Product Name	Number of		Product Family Code
		light sources	Optic type	
911401640505	DN140B LED20S/840 C ELB3 IA1	-	High-gloss mirror	-
911401632605	DN140B LED10S/830 PSU WR IP54 PI6	-	White reflector without louver	-
911401632705	DN140B LED10S/840 PSU WR IP54 PI6	-	White reflector without louver	-
911401632805	DN140B LED10S/830 PSED-E WR IP54	-	White reflector without louver	-
911401632905	DN140B LED10S/840 PSED-E WR IP54	-	White reflector without louver	-
911401633005	DN140B LED20S/830 PSU WR IP54 PI6	-	White reflector without louver	-
911401633105	DN140B LED20S/840 PSU WR IP54 PI6	-	White reflector without louver	-
911401633205	DN140B LED20S/830 PSED-E WR IP54	-	White reflector without louver	-
911401633305	DN140B LED20S/840 PSED-E WR IP54	-	White reflector without louver	-
911401633405	DN140B LED10S/830 PSU C IP54 PI6	-	High-gloss mirror	-
911401633505	DN140B LED10S/840 PSU C IP54 PI6	-	High-gloss mirror	-
911401633605	DN140B LED10S/830 PSED-E C IP54	-	High-gloss mirror	-
911401633705	DN140B LED10S/840 PSED-E C IP54	-	High-gloss mirror	-
911401633805	DN140B LED20S/830 PSU C IP54 PI6	-	High-gloss mirror	-
911401633905	DN140B LED20S/840 PSU C IP54 PI6	-	High-gloss mirror	-
911401634005	DN140B LED20S/830 PSED-E C IP54	-	High-gloss mirror	-
911401634105	DN140B LED20S/840 PSED-E C IP54	-	High-gloss mirror	-

Initial Performance (IEC Compliant) (1/2)

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering	
				Index	Initial LED luminaire efficacy
910500457699	DN130B LED10S/83 0 PSU PI6 WH	(0.43, 0.40)	3000 K	80	100 lm/W
910500457701	DN130B LED10S/83 0 PSED-E II WH	(0.43, 0.40)	3000 K	80	100 lm/W
910500457724	DN130B LED10S/84 SDCM <5	(0.38, 0.37)	4000 K	80	100 lm/W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering	
				Index	Initial LED luminaire efficacy
910500457725	DN130B LED10S/84 0 PSED-E II WH	(0.38, 0.37)	4000 K	80	100 lm/W
910500458078	DN130B LED10S/83 0 PSU	(0.43, 0.40)	3000 K	80	100 lm/W

CoreLine Downlight

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy
	IP44 PI6 WH				
910500458079	DN130B LED10S/84 0 PSU IP44 PI6 WH	(0.38, 0.37) SDCM <5	4000 K	80	100 lm/W
910500458080	DN130B LED10S/83 0 PSED-E IP44 II WH	(0.43, 0.40) SDCM <5	3000 K	80	100 lm/W
910500458081	DN130B LED10S/84 0 PSED-E IP44 II WH	(0.38, 0.37) SDCM <5	4000 K	80	100 lm/W
910500457702	DN130B LED20S/83 0 PSU PI6 WH	(0.43, 0.40) SDCM <5	3000 K	80	95 lm/W
910500457703	DN130B LED20S/83 0 PSED-E II WH	(0.43, 0.40) SDCM <5	3000 K	80	95 lm/W
910500457726	DN130B LED20S/84 0 PSU PI6 WH	(0.38, 0.37) SDCM <5	4000 K	80	95 lm/W
910500457727	DN130B LED20S/84 0 PSED-E II WH	(0.38, 0.37) SDCM <5	4000 K	80	95 lm/W
910500458083	DN130B LED20S/84 0 PSU IP44 PI6 WH	(0.38, 0.37) SDCM <5	4000 K	80	95 lm/W
910500458084	DN130B LED20S/83 0 PSED-E IP44 II WH	(0.43, 0.40) SDCM <5	3000 K	80	95 lm/W
910500458085	DN130B LED20S/84 0 PSED-E IP44 II WH	(0.38, 0.37) SDCM <5	4000 K	80	95 lm/W
910500465262	DN130B LED20S/83 0 IA1 WH	(0.43, 0.40) SDCM <5	3000 K	80	90 lm/W
910500465263	DN130B LED20S/84 0 IA1 WH	(0.38, 0.37) SDCM <5	4000 K	80	90 lm/W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy
910500465338	DN130B LED20S/83 0 ELB3 IA1 WH	(0.43, 0.40) SDCM <5	3000 K	80	80 lm/W
910500465339	DN130B LED20S/84 0 ELB3 IA1 WH	(0.38, 0.37) SDCM <5	4000 K	80	80 lm/W
910500457704	DN131B LED10S/83 0 PSU PI6 ALU	(0.43, 0.40) SDCM <5	3000 K	80	100 lm/W
910500457705	DN131B LED10S/83 0 PSED-E II ALU	(0.43, 0.40) SDCM <5	3000 K	80	100 lm/W
910500457728	DN131B LED10S/84 0 PSU PI6 ALU	(0.38, 0.37) SDCM <5	4000 K	80	100 lm/W
910500457729	DN131B LED10S/84 0 PSED-E II ALU	(0.38, 0.37) SDCM <5	4000 K	80	100 lm/W
910500458086	DN131B LED10S/83 0 PSU IP44 PI6 ALU	(0.43, 0.40) SDCM <5	3000 K	80	100 lm/W
910500458087	DN131B LED10S/84 0 PSU IP44 PI6 ALU	(0.38, 0.37) SDCM <5	4000 K	80	100 lm/W
910500458089	DN131B LED10S/84 0 PSED-E IP44 II ALU	(0.38, 0.37) SDCM <5	4000 K	80	100 lm/W
910500457706	DN131B LED20S/83 0 PSU PI6 ALU	(0.43, 0.40) SDCM <5	3000 K	80	95 lm/W
910500457707	DN131B LED20S/83 0 PSED-E II ALU	(0.43, 0.40) SDCM <5	3000 K	80	95 lm/W
910500457730	DN131B LED20S/84 0 PSU PI6 ALU	(0.38, 0.37) SDCM <5	4000 K	80	95 lm/W

CoreLine Downlight

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy
910500457731	DN131B LED20S/84 0 PSED-E II ALU	(0.38, 0.37)	4000 K	80	95 lm/W
910500458090	DN131B LED20S/83 0 PSU IP44 PI6 ALU	(0.43, 0.40)	3000 K	80	95 lm/W
910500458091	DN131B LED20S/84 0 PSU IP44 PI6 ALU	(0.38, 0.37)	4000 K	80	95 lm/W
910500458092	DN131B LED20S/83 0 PSED-E IP44 II ALU	(0.43, 0.40)	3000 K	80	95 lm/W
910500458093	DN131B LED20S/84 0 PSED-E IP44 II ALU	(0.38, 0.37)	4000 K	80	95 lm/W
910500465264	DN131B LED20S/83 0 IA1 ALU	(0.43, 0.40)	3000 K	80	90 lm/W
910500465265	DN131B LED20S/84 0 IA1 ALU	(0.38, 0.37)	4000 K	80	90 lm/W
910500465340	DN131B LED20S/83 0 ELB3 IA1 ALU	(0.43, 0.40)	3000 K	80	80 lm/W
910500465341	DN131B LED20S/84 0 ELB3 IA1 ALU	(0.38, 0.37)	4000 K	80	80 lm/W
911401631005	DN140B LED10S/83 0 PSU WR PI6	(0.435,0.405)	3000 K	≥80	116 lm/W
911401631105	DN140B LED10S/84 0 PSU WR PI6	(0.381,0.379)	4000 K	≥80	116 lm/W
911401631205	DN140B LED10S/83 0 PSED-E WR	(0.435,0.405)	3000 K	≥80	96 lm/W
911401631305	DN140B LED10S/84 SDCM≤5	(0.381,0.379)	4000 K	≥80	96 lm/W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy
	0 PSED-E WR				
911401639405	DN140B LED10S/83 0 PSED-E WR ELB3	(0.435,0.405)	3000 K	≥80	95.65217391304348 lm/W
911401639505	DN140B LED10S/84 0 PSED-E WR ELB3	(0.381,0.379)	4000 K	≥80	95.65217391304348 lm/W
911401631405	DN140B LED20S/83 0 PSU WR PI6	(0.435,0.404)	3000 K	≥80	116 lm/W
911401631505	DN140B LED20S/84 0 PSU WR PI6	(0.380,0.377)	4000 K	≥80	116 lm/W
911401631605	DN140B LED20S/83 0 PSED-E WR	(0.435,0.404)	3000 K	≥80	107 lm/W
911401631705	DN140B LED20S/84 0 PSED-E WR	(0.380,0.377)	4000 K	≥80	107 lm/W
911401634205	DN140B LED20S/83 0 WR IA1	(0.435,0.404)	3000 K	≥80	100 lm/W
911401634305	DN140B LED20S/84 0 WR IA1	(0.380,0.377)	4000 K	≥80	100 lm/W
911401639605	DN140B LED20S/83 0 PSED-E WR ELB3	(0.435,0.404)	3000 K	≥80	107.3170731707317 lm/W
911401639705	DN140B LED20S/84 0 PSED-E WR ELB3	(0.380,0.377)	4000 K	≥80	107.3170731707317 lm/W
911401640205	DN140B LED20S/83 0 WR ELB3 IA1	(0.435,0.404)	3000 K	≥80	100 lm/W
911401640305	DN140B LED20S/84 0 WR ELB3 IA1	(0.380,0.377)	4000 K	≥80	100 lm/W
911401631805	DN140B LED10S/83 SDCM≤5	(0.433,0.405)	3000 K	≥80	116 lm/W

CoreLine Downlight

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy
	0 PSU C PI6				
911401631905	DN140B LED10S/84 0 PSU C PI6	(0.379,0.379)	4000 K	≥80	116 lm/W
911401632005	DN140B LED10S/83 0 PSED-E C	(0.433,0.405)	3000 K	≥80	96 lm/W
911401632105	DN140B LED10S/84 0 PSED-E C	(0.379,0.379)	4000 K	≥80	96 lm/W
911401639805	DN140B LED10S/83 0 PSED-E C ELB3	(0.433,0.405)	3000 K	≥80	95.65217391304348 lm/W
911401639905	DN140B LED10S/84 0 PSED-E C ELB3	(0.379,0.379)	4000 K	≥80	95.65217391304348 lm/W
911401632205	DN140B LED20S/83 0 PSU C PI6	(0.432,0.404)	3000 K	≥80	116 lm/W
911401632305	DN140B LED20S/84 0 PSU C PI6	(0.378,0.377)	4000 K	≥80	116 lm/W
911401632405	DN140B LED20S/83 0 PSED-E C	(0.432,0.404)	3000 K	≥80	107 lm/W
911401632505	DN140B LED20S/84 0 PSED-E C	(0.378,0.377)	4000 K	≥80	107 lm/W
911401634405	DN140B LED20S/83 0 C IA1	(0.432,0.404)	3000 K	≥80	100 lm/W
911401634505	DN140B LED20S/84 0 C IA1	(0.378,0.377)	4000 K	≥80	100 lm/W
911401640005	DN140B LED20S/83 0 PSED-E C ELB3	(0.432,0.404)	3000 K	≥80	107.3170731707317 lm/W
911401640105	DN140B LED20S/84 SDCM≤5	(0.378,0.377)	4000 K	≥80	107.3170731707317 lm/W

Order Code	Full Product Name	Initial chromaticity	Init. Corr. Color Temperature	Init. Color Rendering Index	Initial LED luminaire efficacy
	0 PSED-E C ELB3				
911401640405	DN140B LED20S/83 0 C ELB3 IA1	(0.432,0.404)	3000 K	≥80	100 lm/W
911401640505	DN140B LED20S/84 0 C ELB3 IA1	(0.378,0.377)	4000 K	≥80	100 lm/W
911401632605	DN140B LED10S/83 0 PSU WR IP54 PI6	(0.435,0.405)	3000 K	≥80	116 lm/W
911401632705	DN140B LED10S/84 0 PSU WR IP54 PI6	(0.381,0.379)	4000 K	≥80	116 lm/W
911401632805	DN140B LED10S/83 0 PSED-E WR IP54	(0.435,0.405)	3000 K	≥80	96 lm/W
911401632905	DN140B LED10S/84 0 PSED-E WR IP54	(0.381,0.379)	4000 K	≥80	96 lm/W
911401633005	DN140B LED20S/83 0 PSU WR IP54 PI6	(0.435,0.404)	3000 K	≥80	116 lm/W
911401633105	DN140B LED20S/84 0 PSU WR IP54 PI6	(0.380,0.377)	4000 K	≥80	116 lm/W
911401633205	DN140B LED20S/83 0 PSED-E WR IP54	(0.435,0.404)	3000 K	≥80	107 lm/W
911401633305	DN140B LED20S/84 0 PSED-E WR IP54	(0.380,0.377)	4000 K	≥80	107 lm/W
911401633405	DN140B LED10S/83 0 PSU C IP54 PI6	(0.433,0.405)	3000 K	≥80	116 lm/W
911401633505	DN140B LED10S/84 0 PSU C IP54 PI6	(0.379,0.379)	4000 K	≥80	116 lm/W

CoreLine Downlight

Order Code	Full Product	Initial	Init. Corr.	Init. Color	Initial LED luminaire efficacy
	Name	chromaticity	Temperature	Color Rendering Index	
911401633605	DN140B LED10S/83 0 PSED-E C IP54	(0.433,0.405)	3000 K	≥80	96 lm/W
911401633705	DN140B LED10S/84 0 PSED-E C IP54	(0.379,0.379)	4000 K	≥80	96 lm/W
911401633805	DN140B LED20S/83 0 PSU C IP54 PI6	(0.432,0.404)	3000 K	≥80	116 lm/W

Order Code	Full Product	Initial	Init. Corr.	Init. Color	Initial LED luminaire efficacy
	Name	chromaticity	Temperature	Color Rendering Index	
911401633905	DN140B LED20S/84 0 PSU C IP54 PI6	(0.378,0.377)	4000 K	≥80	116 lm/W
911401634005	DN140B LED20S/83 0 PSED-E C IP54	(0.432,0.404)	3000 K	≥80	107 lm/W
911401634105	DN140B LED20S/84 0 PSED-E C IP54	(0.378,0.377)	4000 K	≥80	107 lm/W

Initial Performance (IEC Compliant) (2/2)

Order Code	Full Product Name	Initial luminous flux	Initial input power
910500457699	DN130B LED10S/830 PSU PI6 WH	1100 lm	11 W
910500457701	DN130B LED10S/830 PSED-E II WH	1100 lm	11 W
910500457724	DN130B LED10S/840 PSU PI6 WH	1100 lm	11 W
910500457725	DN130B LED10S/840 PSED-E II WH	1100 lm	11 W
910500458078	DN130B LED10S/830 PSU IP44 PI6 WH	1100 lm	11 W
910500458079	DN130B LED10S/840 PSU IP44 PI6 WH	1100 lm	11 W
910500458080	DN130B LED10S/830 PSED-E IP44 II WH	1100 lm	11 W
910500458081	DN130B LED10S/840 PSED-E IP44 II WH	1100 lm	11 W
910500457702	DN130B LED20S/830 PSU PI6 WH	2100 lm	22 W
910500457703	DN130B LED20S/830 PSED-E II WH	2100 lm	22 W
910500457726	DN130B LED20S/840 PSU PI6 WH	2100 lm	22 W
910500457727	DN130B LED20S/840 PSED-E II WH	2100 lm	22 W
910500458083	DN130B LED20S/840 PSU IP44 PI6 WH	2100 lm	22 W
910500458084	DN130B LED20S/830 PSED-E IP44 II WH	2100 lm	22 W
910500458085	DN130B LED20S/840 PSED-E IP44 II WH	2100 lm	22 W
910500465262	DN130B LED20S/830 IA1 WH	2000 lm	22 W
910500465263	DN130B LED20S/840 IA1 WH	2000 lm	22 W
910500465338	DN130B LED20S/830 ELB3 IA1 WH	2000 lm	25 W
910500465339	DN130B LED20S/840 ELB3 IA1 WH	2000 lm	25 W
910500457704	DN131B LED10S/830 PSU PI6 ALU	1100 lm	11 W
910500457705	DN131B LED10S/830 PSED-E II ALU	1100 lm	11 W
910500457728	DN131B LED10S/840 PSU PI6 ALU	1100 lm	11 W
910500457729	DN131B LED10S/840 PSED-E II ALU	1100 lm	11 W
910500458086	DN131B LED10S/830 PSU IP44 PI6 ALU	1100 lm	11 W

Order Code	Full Product Name	Initial luminous flux	Initial input power
910500458087	DN131B LED10S/840 PSU IP44 PI6 ALU	1100 lm	11 W
910500458089	DN131B LED10S/840 PSED-E IP44 II ALU	1100 lm	11 W
910500457706	DN131B LED20S/830 PSU PI6 ALU	2100 lm	22 W
910500457707	DN131B LED20S/830 PSED-E II ALU	2100 lm	22 W
910500457730	DN131B LED20S/840 PSU PI6 ALU	2100 lm	22 W
910500457731	DN131B LED20S/840 PSED-E II ALU	2100 lm	22 W
910500458090	DN131B LED20S/830 PSU IP44 PI6 ALU	2100 lm	22 W
910500458091	DN131B LED20S/840 PSU IP44 PI6 ALU	2100 lm	22 W
910500458092	DN131B LED20S/830 PSED-E IP44 II ALU	2100 lm	22 W
910500458093	DN131B LED20S/840 PSED-E IP44 II ALU	2100 lm	22 W
910500465264	DN131B LED20S/830 IA1 ALU	2000 lm	22 W
910500465265	DN131B LED20S/840 IA1 ALU	2000 lm	22 W
910500465340	DN131B LED20S/830 ELB3 IA1 ALU	2000 lm	25 W
910500465341	DN131B LED20S/840 ELB3 IA1 ALU	2000 lm	25 W
911401631005	DN140B LED10S/830 PSU WR PI6	1100 lm	9.5 W
911401631105	DN140B LED10S/840 PSU WR PI6	1100 lm	9.5 W
911401631205	DN140B LED10S/830 PSED-E WR	1100 lm	11.5 W
911401631305	DN140B LED10S/840 PSED-E WR	1100 lm	11.5 W
911401639405	DN140B LED10S/830 PSED-E WR ELB3	1100 lm	11.5 W
911401639505	DN140B LED10S/840 PSED-E WR ELB3	1100 lm	11.5 W
911401631405	DN140B LED20S/830 PSU WR PI6	2200 lm	19 W
911401631505	DN140B LED20S/840 PSU WR PI6	2200 lm	19 W
911401631605	DN140B LED20S/830 PSED-E WR	2200 lm	20.5 W
911401631705	DN140B LED20S/840 PSED-E WR	2200 lm	20.5 W
911401634205	DN140B LED20S/830 WR IA1	2200 lm	22 W

CoreLine Downlight

Order Code	Full Product Name	Initial luminous flux	Initial input power
911401634305	DN140B LED20S/840 WR IA1	2200 lm	22 W
911401639605	DN140B LED20S/830 PSED-E WR ELB3	2200 lm	20.5 W
911401639705	DN140B LED20S/840 PSED-E WR ELB3	2200 lm	20.5 W
911401640205	DN140B LED20S/830 WR ELB3 IA1	2200 lm	22 W
911401640305	DN140B LED20S/840 WR ELB3 IA1	2200 lm	22 W
911401631805	DN140B LED10S/830 PSU C PI6	1100 lm	9.5 W
911401631905	DN140B LED10S/840 PSU C PI6	1100 lm	9.5 W
911401632005	DN140B LED10S/830 PSED-E C	1100 lm	11.5 W
911401632105	DN140B LED10S/840 PSED-E C	1100 lm	11.5 W
911401639805	DN140B LED10S/830 PSED-E C ELB3	1100 lm	11.5 W
911401639905	DN140B LED10S/840 PSED-E C ELB3	1100 lm	11.5 W
911401632205	DN140B LED20S/830 PSU C PI6	2200 lm	19 W
911401632305	DN140B LED20S/840 PSU C PI6	2200 lm	19 W
911401632405	DN140B LED20S/830 PSED-E C	2200 lm	20.5 W
911401632505	DN140B LED20S/840 PSED-E C	2200 lm	20.5 W
911401634405	DN140B LED20S/830 C IA1	2200 lm	22 W
911401634505	DN140B LED20S/840 C IA1	2200 lm	22 W
911401640005	DN140B LED20S/830 PSED-E C ELB3	2200 lm	20.5 W
911401640105	DN140B LED20S/840 PSED-E C ELB3	2200 lm	20.5 W
911401640405	DN140B LED20S/830 C ELB3 IA1	2200 lm	22 W

Order Code	Full Product Name	Initial luminous flux	Initial input power
911401640505	DN140B LED20S/840 C ELB3 IA1	2200 lm	22 W
911401632605	DN140B LED10S/830 PSU WR IP54 PI6	1100 lm	9.5 W
911401632705	DN140B LED10S/840 PSU WR IP54 PI6	1100 lm	9.5 W
911401632805	DN140B LED10S/830 PSED-E WR IP54	1100 lm	11.5 W
911401632905	DN140B LED10S/840 PSED-E WR IP54	1100 lm	11.5 W
911401633005	DN140B LED20S/830 PSU WR IP54 PI6	2200 lm	19 W
911401633105	DN140B LED20S/840 PSU WR IP54 PI6	2200 lm	19 W
911401633205	DN140B LED20S/830 PSED-E WR IP54	2200 lm	20.5 W
911401633305	DN140B LED20S/840 PSED-E WR IP54	2200 lm	20.5 W
911401633405	DN140B LED10S/830 PSU C IP54 PI6	1100 lm	9.5 W
911401633505	DN140B LED10S/840 PSU C IP54 PI6	1100 lm	9.5 W
911401633605	DN140B LED10S/830 PSED-E C IP54	1100 lm	11.5 W
911401633705	DN140B LED10S/840 PSED-E C IP54	1100 lm	11.5 W
911401633805	DN140B LED20S/830 PSU C IP54 PI6	2200 lm	19 W
911401633905	DN140B LED20S/840 PSU C IP54 PI6	2200 lm	19 W
911401634005	DN140B LED20S/830 PSED-E C IP54	2200 lm	20.5 W
911401634105	DN140B LED20S/840 PSED-E C IP54	2200 lm	20.5 W

Mechanical and Housing

Order Code	Full Product Name	Color
910500457699	DN130B LED10S/830 PSU PI6 WH	White
910500457701	DN130B LED10S/830 PSED-E II WH	White
910500457724	DN130B LED10S/840 PSU PI6 WH	White
910500457725	DN130B LED10S/840 PSED-E II WH	White
910500458078	DN130B LED10S/830 PSU IP44 PI6 WH	White
910500458079	DN130B LED10S/840 PSU IP44 PI6 WH	White
910500458080	DN130B LED10S/830 PSED-E IP44 II WH	White
910500458081	DN130B LED10S/840 PSED-E IP44 II WH	White
910500457702	DN130B LED20S/830 PSU PI6 WH	White
910500457703	DN130B LED20S/830 PSED-E II WH	White
910500457726	DN130B LED20S/840 PSU PI6 WH	White
910500457727	DN130B LED20S/840 PSED-E II WH	White
910500458083	DN130B LED20S/840 PSU IP44 PI6 WH	White
910500458084	DN130B LED20S/830 PSED-E IP44 II WH	White
910500458085	DN130B LED20S/840 PSED-E IP44 II WH	White
910500465262	DN130B LED20S/830 IA1 WH	White
910500465263	DN130B LED20S/840 IA1 WH	White
910500465338	DN130B LED20S/830 ELB3 IA1 WH	White
910500465339	DN130B LED20S/840 ELB3 IA1 WH	White
910500457704	DN131B LED10S/830 PSU PI6 ALU	Aluminum
910500457705	DN131B LED10S/830 PSED-E II ALU	Aluminum
910500457728	DN131B LED10S/840 PSU PI6 ALU	Aluminum
910500457729	DN131B LED10S/840 PSED-E II ALU	Aluminum
910500458086	DN131B LED10S/830 PSU IP44 PI6 ALU	Aluminum
910500458087	DN131B LED10S/840 PSU IP44 PI6 ALU	Aluminum

Order Code	Full Product Name	Color
910500458089	DN131B LED10S/840 PSED-E IP44 II ALU	Aluminum
910500457706	DN131B LED20S/830 PSU PI6 ALU	Aluminum
910500457707	DN131B LED20S/830 PSED-E II ALU	Aluminum
910500457730	DN131B LED20S/840 PSU PI6 ALU	Aluminum
910500457731	DN131B LED20S/840 PSED-E II ALU	Aluminum
910500458090	DN131B LED20S/830 PSU IP44 PI6 ALU	Aluminum
910500458091	DN131B LED20S/840 PSU IP44 PI6 ALU	Aluminum
910500458092	DN131B LED20S/830 PSED-E IP44 II ALU	Aluminum
910500458093	DN131B LED20S/840 PSED-E IP44 II ALU	Aluminum
910500465264	DN131B LED20S/830 IA1 ALU	Aluminum
910500465265	DN131B LED20S/840 IA1 ALU	Aluminum
910500465340	DN131B LED20S/830 ELB3 IA1 ALU	Aluminum
910500465341	DN131B LED20S/840 ELB3 IA1 ALU	Aluminum
911401631005	DN140B LED10S/830 PSU WR PI6	Black and white
911401631105	DN140B LED10S/840 PSU WR PI6	Black and white
911401631205	DN140B LED10S/830 PSED-E WR	Black and white
911401631305	DN140B LED10S/840 PSED-E WR	Black and white
911401639405	DN140B LED10S/830 PSED-E WR ELB3	Black and white
911401639505	DN140B LED10S/840 PSED-E WR ELB3	Black and white
911401631405	DN140B LED20S/830 PSU WR PI6	Black and white
911401631505	DN140B LED20S/840 PSU WR PI6	Black and white
911401631605	DN140B LED20S/830 PSED-E WR	Black and white
911401631705	DN140B LED20S/840 PSED-E WR	Black and white
911401634205	DN140B LED20S/830 WR IA1	Black and white
911401634305	DN140B LED20S/840 WR IA1	Black and white

CoreLine Downlight

Order Code	Full Product Name	Color
911401639605	DN140B LED20S/830 PSED-E WR ELB3	Black and white
911401639705	DN140B LED20S/840 PSED-E WR ELB3	Black and white
911401640205	DN140B LED20S/830 WR ELB3 IA1	Black and white
911401640305	DN140B LED20S/840 WR ELB3 IA1	Black and white
911401631805	DN140B LED10S/830 PSU C PI6	Black and white
911401631905	DN140B LED10S/840 PSU C PI6	Black and white
911401632005	DN140B LED10S/830 PSED-E C	Black and white
911401632105	DN140B LED10S/840 PSED-E C	Black and white
911401639805	DN140B LED10S/830 PSED-E C ELB3	Black and white
911401639905	DN140B LED10S/840 PSED-E C ELB3	Black and white
911401632205	DN140B LED20S/830 PSU C PI6	Black and white
911401632305	DN140B LED20S/840 PSU C PI6	Black and white
911401632405	DN140B LED20S/830 PSED-E C	Black and white
911401632505	DN140B LED20S/840 PSED-E C	Black and white
911401634405	DN140B LED20S/830 C IA1	Black and white
911401634505	DN140B LED20S/840 C IA1	Black and white
911401640005	DN140B LED20S/830 PSED-E C ELB3	Black and white
911401640105	DN140B LED20S/840 PSED-E C ELB3	Black and white

Order Code	Full Product Name	Color
911401640405	DN140B LED20S/830 C ELB3 IA1	Black and white
911401640505	DN140B LED20S/840 C ELB3 IA1	Black and white
911401632605	DN140B LED10S/830 PSU WR IP54 PI6	Black and white
911401632705	DN140B LED10S/840 PSU WR IP54 PI6	Black and white
911401632805	DN140B LED10S/830 PSED-E WR IP54	Black and white
911401632905	DN140B LED10S/840 PSED-E WR IP54	Black and white
911401633005	DN140B LED20S/830 PSU WR IP54 PI6	Black and white
911401633105	DN140B LED20S/840 PSU WR IP54 PI6	Black and white
911401633205	DN140B LED20S/830 PSED-E WR IP54	Black and white
911401633305	DN140B LED20S/840 PSED-E WR IP54	Black and white
911401633405	DN140B LED10S/830 PSU C IP54 PI6	Black and white
911401633505	DN140B LED10S/840 PSU C IP54 PI6	Black and white
911401633605	DN140B LED10S/830 PSED-E C IP54	Black and white
911401633705	DN140B LED10S/840 PSED-E C IP54	Black and white
911401633805	DN140B LED20S/830 PSU C IP54 PI6	Black and white
911401633905	DN140B LED20S/840 PSU C IP54 PI6	Black and white
911401634005	DN140B LED20S/830 PSED-E C IP54	Black and white
911401634105	DN140B LED20S/840 PSED-E C IP54	Black and white

